



CABLECAST SX2HD MULTI-FORMAT HD/SD MULTI-OUTPUT VIDEO SERVER



The Cablecast SX2HD video servers flat out perform. A multi-format video server, it will play out and encode a wide variety of HD and SD codecs. This beast has two output channels, one encoder channel, 18 useable terabytes of RAID5 storage and built-in channel branding.

WHY USE THE CABLECAST SX2HD?

- **Saves you time and Money** - Cablecast SX Video servers will play almost any format your producers submit. MPEG-2, WMV, H.264, AVI, DVCPROHD, ProRes, no transcoding is necessary, just schedule and air.
- **Down-Converts HD to SD and Up-Converts SD to HD** - The Cablecast HD video servers will down-convert your HD files automatically for playout onto your SD cable channel, or up-convert your SD files for playout in HD.
- **Continual Promotion** – Cablecast automatically promotes your programs on your Carousel bulletin board, your website, in TV-Guide and in programming reports.
- **Integrated Video Overlays for Channel Branding** - A station bug for branding your channel. Bug text which you can run in a different corner simultaneously. And a super smooth crawl with both background and foreground graphics.

KEY FEATURES

- Two output channels and one encoder channel of SDI or HD-SDI with embedded audio and sixteen terabytes of usable storage included.
- Complete scheduling and automation with deck and device control
- Tightly integrated with Carousel to provide your community with weather forecasts, traffic cams, RSS feeds, community announcements, and other essential community information.
- Carousel also pulls the schedule from Cablecast to automatically generate “Coming up Next”, “See it Again” and other promotional messages throughout the day.
- Free support for the life of the server.

SPECIFICATIONS

Network:	10/100/1000base-TX	
Power:	100-240V AC, 50/60Hz	
Power Consumption:	approx. 300w	
Power Supply:	Redundant Power	
Dimensions:	19" x 26" x 5.25" (3RU)	
Weight:	83lbs. (Shipping)	
Hard Disk:	18TB RAID5 - Content	500GB RAID1 - System
Video Inputs:	1 SDI / HD-SDI (BNC) (no analog video)	
Audio Inputs:	1 Pair AES / EBU	1 Pair SDI stereo embedded (no analog audio)
Video Outputs:	2 SDI / HD-SDI (no analog video)	
Audio Outputs:	2 Pair AES / EBU	2 Pair SDI stereo embedded (no analog audio)
Genlock:	Tri-Level Sync or Analog Blackburst	
Encoding Formats:	SD: MPEG 2 IBP, MPEG 2 I-Frame, DVCAM, DVCPRO HD: MPEG 2 I-Frame & IBP, DVCPRO HD, ProRes (422LT, 422 and 422HQ)	
Playback Formats:	SD: MPEG-2 IBP, MPEG 2 I-Frame, MPEG-4, H.264 (AAC audio only), AVI, DVCAM, DVCPRO, DVCPRO50, DV, IMX HD: MPEG-2 I-Frame & IBP, DVCPRO HD, H.264, XDCAM (SD, HD, HD422, EX), IMX, ProRes (422LT, 422, 422HQ, 422 Proxy)	

800 Transfer Road, Suite 1B Saint Paul, MN. USA 55114

+1 612-866-4118 www.trms.com

©2014 Tightrope Media Systems Corporation. All rights reserved. Tightrope Media Systems, Cablecast and Front Door are registered trademarks of Tightrope Media Systems. All other brand names or marks are used for identification purposes and are trademarks of their respective owners.

CBL-SX2HD-OCT2014